



## TR64 Hookup Wire UL Style 1007

**Conductor** : Solid annealed tinned copper  
**Insulation** : Colour coded PVC  
**Temperature** : -15C to +90C CSA , 80C UL  
**Applications** : Internal wiring of electrical and electronic equipment, panels and meters.  
**Approvals** : CSA C22.2 No. 127 FT1, UL AWM subject 758 VW-1  
**Packaging** : 75m, 150m & 300m spools, long length reels.

Product Code	Cond. Size	Cond. Strand	Nom. Insul. Thickness	Suggested Working Voltage	Nom. O.D.	Ship. Weight
			inches		inches	lbs/mft
34H2601	26	SOLID	.015	300	.047	2
34H2401	24	SOLID	.015	300	.052	3
34H2201	22	SOLID	.015	300	.057	4
34H2001	20	SOLID	.015	300	.064	5
34H1801	18	SOLID	.015	300	.072	7
34H1601	16	SOLID	.015	300	.083	10
34H2607	26	7	.015	300	.050	2
34H2407	24	7	.015	300	.056	3
34H2207	22	7	.015	300	.062	4
34H2010	20	10	.015	300	.070	5
34H1816	18	16	.015	300	.079	7
34H1626	16	26	.015	300	.092	10