



AWM SR-PVC Hook-up Wire UL Style 1061

- Conductor** : Soft annealed tinned copper
Insulation : Colour coded PVC
Temperature : -150C CSA, 90C UL
Applications : Internal wiring of electrical and electronic equipment, panels and meters.
Approvals : CSA C22.2 No. 210.2 FT1, UL AWM subject 758 VW-1
Packaging : 75m, 150m & 300m spools, long length reels.

Product Code	Cond. Size	Cond. Strand	Nom. Insul. Thickness	Suggested Working Voltage	Nom. O.D.	Ship. Weight
			inches		inches	lbs/mft
34J2601	26	SOLID	.010	300	.037	1
34J2401	24	SOLID	.010	300	.041	2
34J2607	26	7	.010	300	.040	1
34J2407	24	7	.010	300	.045	2
34J2207	22	7	.010	300	.052	3
34J2007	20	7	.010	300	.060	4
34J2010	20	10	.010	300	.060	5
34J1819	18	19	.010	300	.072	6
34J1619	16	19	.010	300	.081	7



▣ Type B MIL-W-16878 Hook-up Wire

- Conductor** : Soft annealed tinned copper
Insulation : Colour coded PVC
Temperature : -54C bend to +150C
Applications : Internal wiring of electrical and electronic equipment, panels and meters.
Packaging : 75m, 150m & 300m spools, long length reels

Product Code	Cond. Size	Cond. Strand	Nom. Insul. Thickness	Suggested Working Voltage	Nom. O.D.	Ship. Weight
			inches		inches	lbs/mft
34K2601	26	SOLID	.010	600	.037	1
34K2401	24	SOLID	.010	600	.041	2
34K2201	22	SOLID	.010	600	.046	3
34K2001	20	SOLID	.010	600	.054	4
34K1801	18	SOLID	.010	600	.062	7
34K1601	16	SOLID	.010	600	.073	9
34K2607	26	7	.010	600	.040	1
34K2407	24	7	.010	600	.045	2
34K2207	22	7	.010	600	.052	3
34K1807	18	7	.010	600	.060	4
34K1816	18	16	.010	600	.068	7
34K1816	18	16	.010	600	.069	7
34K2219	22	19	.010	600	.054	3
34K2019	20	19	.010	600	.062	4
34K1619	16	19	.010	600	.079	9
34K1419	14	19	.010	600	.093	10