



SVT 60C Vacuum Cleaner Cord

- Conductor** : Bare flexible annealed copper ASTM B-174
Insulation : Colour coded PVC
Jacket : White or Black PVC
Temperature : -20C to +60C
Voltage : 300V
Applications : Designed for use with vacuum cleaners, portable tools & lights, food mixers.
Approvals : CSA C22.2 No. 49 FT1/FT2, UL-62
Packaging : 75m spools.
Colour Code : 2c -Black, White, 3c-Black, White, Green
 * Green Conductor used for grounding purposes only

Product Code	Cond. Size	# of Cond.	Cond. Strand	Nom. Insul. Thickness (Inches)	Nom. Jacket Thickness (Inches)	Nom. O.D. (Inches)	AMPS*	Ship. Weight Lbs/Mft
13E1802	18	2	41	.015	.030	.245	10	37
13E1803	18	3	41	.015	.030	.245	10	39

* Ampacities (Amps per conductor) are based on 30C ambient temperature in air, 90C conductor temperature.

SVT 105C Vacuum Cleaner Cord

- Conductor** : Bare flexible annealed copper ASTM B-174
Insulation : Colour coded PVC
Jacket : White or Black PVC
Temperature : -20C to +105C
Voltage : 300V
Applications : Designed for use with vacuum cleaners, portable tools & lights, food mixers.
Approvals : CSA C22.2 No. 49 FT1/FT2, UL-62
Packaging : 75m spools.
Colour Code : 2c -Black, White, 3c-Black, White, Green
 * Green Conductor used for grounding purposes only

Product Code	Cond. Size	# of Cond.	Cond. Strand	Nom. Insul. Thickness (Inches)	Nom. Jacket Thickness (Inches)	Nom. O.D. (Inches)	AMPS*	Ship. Weight Lbs/Mft
13F1802	18	2	41	.015	.030	.245	10	37
13F1803	18	3	41	.015	.030	.245	10	39

* Ampacities (Amps per conductor) are based on 30C ambient temperature in air, 90C conductor temperature.