



Flat Festoon Cable

- Conductor** : Bare extra flexible soft annealed copper
Insulation : Colour coded PVC
Jacket : Yellow PVC
Temperature : -40C to +105C
Voltage : 600V
Applications : Designed for overhead cranes, hoists, monorails and other industrial applications.
Approvals : CSA, UL
Packaging : 300m spools, Long length Reels cut to length.
Colour Code : Nema standard (Chart 17)

| Product Code | Cond. Size | # of Cond. | Cond. Strand | AMPS* Continuous Duty Rating at 30C Ambient | Amps Short Time Rating 60 Min. | Amps Short Time Rating 30 Min. | Nom. O.D. (Inches) | Ship. Weight Lbs/Mft |
|--------------|------------|------------|--------------|------------------------------------------------------|--------------------------------------------|--------------------------------------------|-----------------------|----------------------------|
| 15B1608 | 16 | 8 | 65 | 15 | N/A | N/A | .222 x 1.180 | 180 |
| 15B1612 | 16 | 12 | 65 | 15 | N/A | N/A | .225 x 1.680 | 280 |
| 15B1404 | 14 | 4 | 41 | 25 | 31 | 32 | .280 x 0.690 | 120 |
| 15B1408 | 14 | 8 | 41 | 17 | N/A | N/A | .280 x 1.280 | 180 |
| 15B1412 | 14 | 12 | 41 | 17 | N/A | N/A | .225 x 1.820 | 340 |
| 15B1204 | 12 | 4 | 65 | 30 | 36 | 40 | .250 x .0800 | 120 |
| 15B1207 | 12 | 7 | 65 | 21 | N/A | N/A | .280 x 1.250 | 290 |
| 15B1208 | 12 | 8 | 65 | 20 | N/A | N/A | .280 x 1.400 | 310 |
| 15B1004 | 10 | 4 | 105 | 40 | 49 | 52 | .276 x 0.880 | 240 |
| 15B0804 | 8 | 4 | 168 | 50 | 63 | 69 | .360 x 1.230 | 450 |
| 15B0604 | 6 | 4 | 266 | 75 | 83 | 94 | .470 x 1.505 | 580 |
| 15B0404 | 4 | 4 | 420 | 95 | 111 | 130 | .550 x 1.720 | 750 |
| 15B0204 | 2 | 4 | 665 | 130 | 148 | 173 | .580 x 2.020 | 950 |

* Ampacities (Amps per conductor) are based on 30C ambient temperature in air, 90C conductor temperature.