



Type PPC/SC Stage & Lighting Entertainment Cable

- Conductor** : Flexible stranded bare annealed copper
- Jacket** : Black oil and weather resistant CSPE thermoset
- Temperature** : -50°C to +105°C (UL 105°C)
- Voltage** : 600V
- Applications** : Designed for portable power and lighting applications in the entertainment industry including motion picture, television, theatres, stage and similar locations. Suitable for both indoor and outdoor uses.
- Approvals** : CSA FT5 Type PPC C22.2 No. 96, UL Type SC Subject 1680, IEEE 383, VW-1, MSHA
- Packaging** : Long length Reels cut to length

Product Code	Cond. Size	# of Cond.	Cond. Strand	Nom. O.D. (inches)	Current AMPS	Ship. Weight Lbs/Mft
16FA0801	8	1	168x30	.385	80	110
16FA0601	6	1	259x30	.430	105	152
16FA0401	4	1	418x30	.475	140	215
16FA0201	2	1	646x30	.540	190	296
16FA01	1/0	1	1032x30	.615	260	424
16FA001	2/0	1	1290x30	.655	300	513
16FA00001	4/0	1	2066x30	.780	405	824

* Ampacities (Amps per conductor) are based on 30°C ambient temperature in air, 90°C conductor temperature.