

# TEW TINNED

## CSA/UL

- Conductor** Tinned copper
- Insulation** 600V Colour coded PVC
- Temperature** -30°C to 105°C
- Approvals** Certified to CSA standard C22.2 No. 127 Equipment/Lead Wires  
UL recognized AWM as per subject 758  
Passes CSA/FT1 vertical flame test  
Passes UL-VW-1 vertical flame test  
UL Style 1015/1230
- Applications** For use in internal wiring of electrical and electronic equipment, point to point wiring, and internal wiring of panels and meters.
- Packaging** X 150, X 300, X 1500 m, Cut to length



Product Code	AWG Size	Stranding	Insulation Thickness (inches)	Nominal O.D. (inches)	Cable Weight (lbs/mft)
34B2207	22	7	0.030	0.093	6
34B2010	20	10	0.030	0.100	7
34B1816	18	16	0.030	0.110	10
34B1626	16	26	0.030	0.123	13
34B1441	14	41	0.030	0.136	19
34B1265	12	65	0.030	0.156	28
34B10104	10	104	0.030	0.196	43
34B08133	8	133	0.045	0.295	68
34B06133	6	133	0.060	0.335	116
34B06266	6	266	0.060	0.335	116
34B04133	4	133	0.060	0.357	167
34B04420	4	420	0.060	0.359	168
34B02665	2	665	0.060	0.451	261
34B01078	1/0	1064	0.080	0.546	436
34B001330	2/0	1330	0.080	0.616	535
34B0001665	3/0	1672	0.080	0.666	638
34B00002107	4/0	2109	0.080	0.709	784

