

INDOOR/OUTDOOR CROSS CONNECT WIRE

CATEGORY 3

Conductor Solid bare copper
Insulation Semi-rigid PVC
Approvals UL444
 Listed as CM
 RoHS-Compliant



Applications Intended for cross connecting points in building entrance enclosures at subscriber's premises and/or in outside Plant (OSP) enclosures.

Product Code	AWG (mm)	Pair Count	Overall Nominal Diameter in (mm)	Approx. Weight lbs/kft (kg/km)	Standard Length ft (m)	Wire Colours
37LA2401	24 (0.51)	1	0.07 (1.8)	3 (7)	1,000 (305)	WHT/BLU
37LA2402	24 (0.51)	2	0.10 (2.5)	6 (13)	1,000 (305)	WHT/BLU WHT/ORG
37LB2401	24 (0.51)	1	0.07 (1.8)	3 (7)	1,000 (305)	YLW/BLU

FLAT SILVER SATIN LINE CORD

Conductor Stranded bare copper
Insulation Colour coded Polypropylene
Jacket Silver Satin PVC
Applications Designed for internal cable of electronic equipment or as handset or telephone cord for subscriber sets.



Product Code	Cond. Size	Pair Count	Cond. Strand	Nominal Insulation Thickness in (mm)	Nominal Jacket Thickness in (mm)	Nominal O.D. (inches)	Nominal O.D. (mm)	Wire Colours
37N2604	26	4	7 x 34	0.010 / 0.23	0.023 / 0.55	0.09 x 0.196	2.5 x 5.0	BLK/RED/ GRN/YLW
37N2606	26	6	7 x 34	0.010 / 0.23	0.024 / 0.60	0.09 x 0.275	2.5 x 5.0	WHT/BLK RED/GRN/ YLW/BLU
37N2608	26	8	7 x 34	0.010 / 0.23	0.025 / 0.70	0.09 x 0.354	2.5 x 5.0	BRN/BLU/YLW/ GRN/RED/BLK/ ORG/GRY