

IN-WALL SPEAKER CABLE

OXYGEN FREE

- Conductor** Stranded bare copper
Insulation 600V semi-rigid PVC
Jacket PVC meter marked blue jacket
Temperature -20°C to 105°C
Approvals CSA File # LL39965
 UL File #E132773, E90540
 RoHS Compliant
 CSA Certified CMG
 Passes CSA/FT4 vertical flame test
Applications For speaker systems where in-wall installation is required.



Product Code	Cond Size	# of Cond.	Cond. Strand	Insulation Thickness (inches)	Jacket Thickness (inches)	Nominal O.D. (inches)	Cable Weight (lbs/mft)	Colour Code
39DB1602	16	2	26/30	0.015	0.025	0.230	31	1
39DB1604	16	4	26/30	0.015	0.025	0.273	53	1
39DB1402	14	2	41/30	0.020	0.030	0.297	49	1
39DB1404	14	4	41/30	0.020	0.030	0.346	87	1

SPEAKER WIRE

1 BARE, 1 TINNED

- Conductor** Stranded bare copper
Insulation Lead free PVC Clear
Assembly Parallel, Integral
Temperature 60°C



Product Code	Cond Size	# of Cond.	Cond. Strand	Insulation Thickness (inches)	Cable Weight (lbs/mft)
39D2002	20	2	10/30	0.010	10
39D1802	18	2	16/30	0.016	21
39D1602	16	2	26/30	0.022	25
39D1402	14	2	41/30	0.028	38