

SVT 60°C VACUUM CLEANER CORD

- Conductor** Bare flexible annealed copper ASTM B-174
 - Insulation** Colour coded PVC
 - Jacket** White or Black PVC
 - Temperature** -20°C to +60°C
 - Voltage** 300V
 - Applications** Designed for use with vacuum cleaners, portable tools & lights, food mixers.
 - Approvals** CSA C22.2 No. 49 FT1/FT2, UL-62, RoHS Compliant
 - Packaging** 75m spools.
 - Colour Code** 2c -Black, White, 3c-Black, White, Green
- *Green Conductor used for grounding purposes only



Product Code	Cond. Size	# of Cond.	Cond. Strand	Nom. Insul. Thickness (Inches)	Nom. Jacket Thickness (Inches)	Nom. O.D. (Inches)	AMPS*	Ship. Weight lbs/mft
13E1802	18	2	41	0.015	0.03	0.245	10	31
13E1803	18	3	41	0.015	0.03	0.250	10	39

*Ampacities (Amps per conductor) are based on 30°C ambient temperature in air, 90°C conductor temperature.

SVT 105°C VACUUM CLEANER CORD

- Conductor** Bare flexible annealed copper ASTM B-174
 - Insulation** Colour coded PVC
 - Jacket** White or Black PVC
 - Temperature** -20°C to +105°C
 - Voltage** 300V
 - Applications** Designed for use with vacuum cleaners, portable tools & lights, food mixers.
 - Approvals** CSA C22.2 No. 49 FT1/FT2, UL-62, RoHS Compliant
 - Packaging** 75m spools.
 - Colour Code** 2c -Black, White, 3c-Black, White, Green
- *Green Conductor used for grounding purposes only



Product Code	Cond. Size	# of Cond.	Cond. Strand	Nom. Insul. Thickness (Inches)	Nom. Jacket Thickness (Inches)	Nom. O.D. (Inches)	AMPS*	Ship. Weight lbs/mft
13F1802	18	2	41	0.015	0.03	0.245	10	1
13F1803	18	3	41	0.015	0.03	0.250	10	39

*Ampacities (Amps per conductor) are based on 30°C ambient temperature in air, 90°C conductor temperature.