

# 1 CONDUCTOR 5KV UNSHIELDED TECK CONNECTORS

# Of Cond.	AMP 30°C Ambient	O-Z Gedney Connectors
4/0	385	JMC100138
250	425	JMC100138
300	480	JMC125163
350	530	JMC125163
400	575	JMC125163
500	660	JMC125163
600	740	JMC125188
750	845	JMC150200
1000	1000	JMC150220

# Of Cond.	AMP 30°C Ambnt	Prysmian WTF*		Nexans WTF*	
		Iberville	T&B	Iberville	T&B
4/0	385	TCA-100-135	10469/ST100-469	TCA-100-135	10469/ST100-469
250	425	TCA-100-135	10469/ST100-469	TCA-100-135	10469/ST100-469
300	480	TCA-125-151	10470/ST100-470	TCA-125-151	10470/ST100-470
350	530	TCA-125-151	10470/ST100-470	TCA-125-151	10470/ST100-470
400	575	TCA-125-151	10470/ST100-470	TCA-125-151	10470/ST100-470
500	660	TCA-125-167	10470/ST100-470	TCA-125-167	10470/ST100-470
600	740	TCA-150-182	10471/ST125-473	TCA-200-231	10473/ST125-473
750	845	TCA-150-208	10472/ST125-472	TCS-150-208	10472/ST125-472
1000	1000	TCA-200-231	10473/ST125-473	TCA-200-231	10473/ST125-473

\*Water Tight Fittings

Other connector types available: Dry, Copper Free Aluminum, Slim Design, Angled  
Ensure that only non-magnetic connectors are used.